

Features

- Real-time transmission over UTP CAT5E/6 cable
- Passive, No power supply required
- Excellent anti-thunder, anti-static and anti-interference capabilities
- Compatible format: HDCVI/TVI/AHD/CVBS
- With 75 ohms BNC male connector, and push-in type terminal connections
- The enclosures are made so that can be joined them to each other

Specification

Transmission Signal	1 CH	1 CH			
Network Cable Type	UTP Cat5E/6				
Transmission Properties	CVBS	max.400m			
	HDCVI	720P ≦ 400m	1080P ≦ 250m	4MP/5MP/8MP(4K) ≤ 200m	
	HDTVI	720P ≦ 350m	1080P ≦ 250m	4MP/5MP/8MP(4K) ≤ 200m	
	AHD	720P ≦ 400m	1080P ≦ 250m	4MP/5MP/8MP(4K) ≦ 190m	
Coaxial Video Connector	BNC Male				
Compatible Format	HDCVI/TVI/AHD/CVBS				
Resolution	720P/1080P/4MP/5MP/4K				
ESD	1a contact discharge electricity level 3, 1b air discharge electricity level 3				
	Per: IEC61000-4-2				
BNC Male Impedance	75 ohms				
UTP Cable Impedance	100 ohms				
Shell	ABS				
Color	Black				